



RENTALS | SALES | SERVICE | PARTS | TOOLING



FEATURED EQUIPMENT



630.365.1649 | rigsource.com

THE RIG SOURCE TOOLBOX

RENT

- Full Rental Fleet
- RS Certified Ready-to-Work Equipment

BUY

- New & Used Equipment
- Customer-Owned Equipment

SUPPORT

- Service (Shop and Field)
- Parts & Tooling
- Remounts & Upgrades

TRUCK-MOUNTED RIGS

DIEDRICH D50 | MACK MD7

Weight | 24,040 lbs

Dimensions | 25'0"L x 8'4"W x 10'9"H

Torque | 9,000 ft-lbs, 600 RPM (MAX)

FEATURES:

Wireline, 3L6 water pump, breakout table and wrench, auger and tool storage



DIEDRICH D70 | MACK MD7

Weight | 27,500 lbs

Dimensions | 27'0"L x 8'5"W x 12'0"H

Torque | 11,200 ft-lbs, 640 RPM (MAX)

FEATURES:

Wireline, heavy duty mast, 3L8 water pump, cathead hoist, slide base and wiggle tail, auger and tool storage



Get a quote or speak to a representative today for latest configurations - [630.365.1649](tel:630.365.1649) or email rentals@rigsourceinc.com or visit rigsource.com

TRACK-MOUNTED RIGS

CME 75 | TERRAMAC RT9

Weight | 32,000 lbs

Dimensions | 25'0"L x 8'4"W x 11'0"H

Torque | 10,445 ft-lbs, 745 RPM

FEATURES:

Wireline, 3L8 water pump, slide base and wiggle tail, auger and tool storage, built-in water tank



CME 750 | BUGGY-MOUNTED

Weight | 21,300 lbs

Dimensions | 22'0"L x 8'0"W x 9'6"H

Torque | 13,786 ft-lbs

FEATURES:

Wireline, 3L8 water pump, breakout table and wrench, auger and tool storage, built-in water tanks



DIEDRICH D90 | IHI IC-50

Weight | 25,000 lbs

Dimensions | 27'0"L x 8'2"W x 11'7"H

Torque | 12,428 ft-lbs, 630 RPM (MAX)

FEATURES:

Wireline, 3L6 water pump, slide base and wiggle tail, breakout table and wrench, auger and tool storage, built-in water tank



Scan here to view our complete rental catalog online!

GEOPROBE® DIRECT PUSH UNITS

GEOPROBE 420 / 540

Weight | 411 lbs (420) / 990 lbs (540)

Dimensions | 420: 5'2"L x 1'11"W x 5'2"H
540: 6'3"L x 2'11"W x 2'5"H

Torque | 345 ft-lbs, 125 RPM (MAX)
(BOTH)



GEOPROBE 6011

Weight | 4,800 lbs

Dimensions | 8'10"L x 4'0"W x 6'5"H

Torque | 560 ft-lbs, 200 RPM (MAX)

FEATURES:

Tier 4, load sense hydraulics,
GH63 hammer for 5' tooling



GEOPROBE 7822 CORE

Weight | 10,200 lbs

Dimensions | 11'1"L x 5'10"W x 8'4"H

Torque | 4,000 ft-lbs, 750 RPM (MAX)

FEATURES:

Dual winch system, breakout table and
wrench, 4 speed head, SPT hammer



GEOPROBE 3126

Weight | 12,600 lbs

Dimensions | 17'10"L x 6'8"W x 9'6"H

Torque | 6-Speed: 6,800 ft-lbs,
720 RPM (MAX)

FEATURES:

Head side shift, SPT Hammer, 6-speed
head, triple winch, 3L6 water pump



GEOPROBE® DIRECT PUSH UNITS (Cont'd)

GEOPROBE 3135GT

Weight | 18,600 lbs

Dimensions | 18'1" L x 6'11" W x 9'7" H (Stowed)

Torque | 10,000 ft-lbs, 1,000 RPM (MAX)

FEATURES:

Centerline head side shift, 6 speed head, triple winch mast, SPT hammer, 3L8 water pump



REMOTE DRILL RIGS

DIEDRICH D50

Weight | 20,500 lbs

Dimensions | 21'0" L x 7'9" W x 8'9" H

Torque | 9,000 ft-lbs, 600 RPM (MAX)

FEATURES:

Wireline, 3L6 water pump, breakout table and wrench



DIEDRICH D70

Weight | 21,700 lbs

Dimensions | 21'0" L x 7'9" W x 9'2" H

Torque | 11,200 ft-lbs, 640 RPM (MAX)

FEATURES:

Wireline, 3L6 water pump, breakout table and wrench, auger and tool storage
(also available in a truck mount)



FRASTE MULTIDRILL

FRASTE SL

Weight | 7,054 lbs*
Dimensions | 16.2' x 4' x 7.5' (stowed)
Tower Height | 16.7'
Max Head Torque | 3,319 ft lb
Max Head Speed | 900 rpm
Rotary Head Torque | 5.9 - 9.2 ft



FRASTE PL A

Weight | 9,479 lbs*
Dimensions | 14.5' x 3.6' x 8.9' (stowed)
Tower Height | 12.5'
Max Head Torque | 2,065 ft lb
Max Head Speed | 800 rpm
Rotary Head Torque | 5.7 ft



FRASTE PL G

Weight | 10,582 lbs*
Dimensions | 17.9' x 6.6' x 8.7' (stowed)
Tower Height | 22.6'
Max Head Torque | 4,204 ft lb
Max Head Speed | 1,000 rpm
Rotary Head Torque | 11.5 ft



*Weight shown as equipped. For the latest configurations, quotes or to speak to a representative, call [630.365.1649](tel:630.365.1649), email rentals@rigsourceinc.com, or visit rigsource.com.

FRASTE MULTIDRILL (CONT'D)

FRASTE ML

Weight | 16,314 lbs*
Dimensions | 20.3' x 7.2' x 9' (stowed)
Tower Height | 29.2'
Max Head Torque | 7,375 ft lb
Max Head Speed | 950 rpm
Rotary Head Torque | 11.5 ft



FRASTE XL 140

Weight | 25,573 lbs*
Dimensions | 24' x 6.6' x 10.3' (stowed)
Tower Height | 32'
Max Head Torque | 11,506 ft lb
Max Head Speed | 910 rpm
Rotary Head Torque | 12.1 ft



LOW CLEARANCE UNITS

DIEDRICH D50LC

Weight | 20,500 lbs
Dimensions | 21'0"L x 7'9"W x 8'9"H
Torque | 9,000 ft-lbs, 600 RPM (MAX)

FEATURES:

Wireline, 3L6 water pump, breakout table and wrench



VERSATRAN RETRIEVER TRUCKS

VERSATRAN 6T

- No CDL Required -Class 6 Chassis
- Up to 12,000lbs Rating for Single Rear-Axle Trucks Depending on Options
- 20'L x 8'6"W bed, Single Stage Ramp
- On GVWR: 26K



VERSATRAN 15T

- CDL Required to operate
- Up to 30,000lbs Rating for Tandem Rear-Axle Trucks
- 24' or 28'L x 8'6"W Bed, Single Stage Ramp



VERSATRAN 20T

- CDL Required
- Up to 40,000 lbs Payload
- Designated for Tri-Axle/Tri-Drive Chassis, capability to mount on Quad Axle
- 28' or 30'L x 8'6"W
- On GVWR: 70K



The



With the largest rental fleet in North America, Rig Source has the equipment you need - when you need it and can meet you where you're at. Our deep experience in drilling and our tireless dedication to customer service means that we will support your rental every step of the way. Our units average less than two years in age and are meticulously maintained and serviced.